

# Jallatte® Spécials

## JALARCHER SAS JJV28

S3 CI HRO SRC  
EN ISO 20345:2011  
38 to 47



- Water-repellent full grain leather
- **Kompact Vibram®** sole
- Antistatic and non-magnetic



- ❖ Ranger type boot, black colour.
- ❖ Bootstrap in water-repellent full grain leather, 1,9 / 2,1 mm thick. Anti-abrasion heel protection and reflecting insert for improved visibility.
- ❖ Ergonomic padded collar and padded ankle protector.
- ❖ Anti-abrasion PU scuff cap. YKK water proof zip for quick release with velcro protection.
- ❖ 3D. Lining. Three dimensional foam structures incorporated within a honeycombed architecture for greater ventilation
- ❖ Confort-Tech footbed : anatomic, antibacterial, shock absorber in the heel area.
- ❖ **Aérane-Tech 200 J**, Perforated toe-cap for perfect foot ventilation. **100 % composite**. Non magnetic, lightweight
- ❖ FleXtane™ By Jallatte anti-perforation inner sole and insert 100 % composite, yielding and flexible, non-detectable, non-magnetic and 70 % lighter than steel. Directly sewn to the bootstrap for 100% protection of the whole surface of the foot. 100% composite materials: lighter than steel, amagnetic, non-conductive of heat and cold
- ❖ **Kompact VIBRAM®** sole , contact heat resistant up to 300° C HRO.

### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011 Requirement SRC (SRA+SRB)

**SRA** Test ground : ceramic/lubricant : water and detergent

On flat 0,40 (>0,32) – On the heel 0,32 (>0,28)

**SRB** Test ground steel/lubricant : glycerine

On flat 0,21 (>0,18) – On the heel: 0,16 (>0,13)

### ◆ Softane™ comfort layer

- ▣ Density = 0.40. Ensures comfortable walking for the wearer. Helps to absorb vibrations and provided heat insulation to the sole of the foot..
- ▣ Ground contact layer in **Néotril™** with **VIBRAM®** system
- ▣ Highly scuff- resistant
- ▣ Heel shock absorbtion > 20 Joules

Weight	Gross weight(42) : 1748 g / Net weight (42) : 1530 g
Size	38 to 47
Packaging	5 pairs
Dimensions	625x425x345



www.jallatte.com