

## CSR2 PULLEY SYSTEM™





The patented locking mechanism in our CSR<sup>2</sup> Pulley™ is easy to release under load, creating much greater efficiency with the lowering and raising necessary to a confined space rescue. The machined aluminum swivels at both ends of the system eliminate any potential twisting of the lines. This system is also an excellent choice for confined space entry or rope access work where a heavy-duty pulley system is desired. Systems comes completed reeved and packed into its storage bag ready to use.

- Strong, lightweight, intuitive design
- Machined from solid block of high-grade aluminum
- Available with either 11 mm (7/16 in) or 12.5 mm (1/2 in) Static-Pro Lifeline
- Systems are UL Classified to NFPA 1983 (2017 ED) General Use
- Individual pulleys are classified to NFPA 1983 General Use and EN 12278
- CSR<sup>2</sup> Pulley and Double Pulley MBS 40 kN (8,992 lbf)
- Includes (2) ProSeries® Aluminum Screw-Lock Carabiners, MBS 47 kN (10,566 lbf) General Use
- Includes 5 ft of 4 mm (5/32 in) nylon accessory cord to remotely control the locking mechanism
- Pat. 7,419,138
- Made in USA

11 mm System Components
11 mm (7/16 in) Static-Pro Lifeline, Blue (1 x 200 ft)
CMC Rope Bag #2, Red
CSR <sup>2</sup> Double Pulley
CSR2 Pulley
ProSeries Aluminum Screw-Lock Carabiner (2)

12.5 mm System Components:
12.5 mm (1/2 in) Static-Pro Lifeline, Red (1 x 200 ft)
CMC Rope Bag #3, Red
CSR <sup>2</sup> Double Pulley

CSR2 Pulley

ProSeries Aluminum Screw-Lock Carabiner (2)

**Option** 11 mm (7/16 in)

**Item** 500103

**PRODUCT NAME** SYSTEM, CSR<sup>2</sup> PULLEY, 11 MM CMC

**PRODUCT WEIGHT** 20.5 LB (9.3 KG)

**COLOR** BLUE

NFPA RATING GENERAL USE

**3 SIGMA MBS** 40 KN (8,992 LBF)

**Option** 12.5 mm (1/2 in)

**Item** 500102

**PRODUCT NAME** SYSTEM, CSR<sup>2</sup> PULLEY, CMC

**PRODUCT WEIGHT** 24.9 LB (11.3 KG)

COLOR RED

NFPA RATING GENERAL USE

**3 SIGMA MBS** 40 KN (8,992 LBF)

1-800-235-5741 info@cmcpro.com cmcpro.com