

**EN 388**

**Abrasion: 3/4**  
**Cut: 1/5**  
**Tear: 2/4**  
**Puncture: 2/4**

**FIELD OF USE :**

Over-gloves are worn over insulating gloves class 00 and 0. They give the mechanical protection of the insulating glove. It's possible to adjust the tightening of the glove to the hand of the user with a Velcro on the back

**CHARACTERISTICS :**

- Made from high quality goatskin.
- Palm and top: silicone treated.
- Large protective cuff in chrome tanned hide (10 cm length)
- American fitting.
- Colours: chrome.
- Designed to be worn with the CG or CGA insulating rubber gloves range class 00 and class 0
- Characteristics according to the standard EN 388.
  - Abrasion: 3/4
  - Cut: 1/5
  - Tear: 2/4
  - Puncture: 2/4
- Dexterity level tested according EN 420: 5 (excellent holding).
- Packing in plastic bag.

References	Sizes	H mm	h mm	L mm
CG-981-08	8	295	195	120
CG-981-09	9	305	205	125
CG-981-10	10	310	210	130
CG-981-11	11	310	210	135




Table: Selection guide according to the size of the insulating rubber gloves

Insulating glove		Over glove	8	9	10	11
		Class 00	8	X		
Class 0	9			X		
	10				X	
	11					X
	8	X				
Class 0	9	X	X			
	10		X	X		
	11			X	X	
	11				X	X