



252

LIQUI-LOK

Zinc-Free Thread-Locking Compound

- GEAR OILS
MOTOR OILS
HYDRAULIC OILS
PIPE COATINGS
THREAD SEALANTS
BEARING GREASES
SPECIALTY GREASES
THREAD COMPOUNDS
SUCKER ROD COATINGS
OUTSIDE PRESERVATIVES
WIRELINE GREASE SEALS
CLEANERS & DEGREASERS
PIPE STORAGE COMPOUNDS
RUST & CORROSION INHIBITORS
THREAD LOCKING COMPOUNDS
VALVE LUBRICANTS & SEALANTS
TOOL JOINT & DRILL COLLAR COMPOUNDS

PRODUCT DESCRIPTION

A zinc-free, thread locking compound, 252 LIQUI-LOK is specially formulated to replace the welding of casing joints and threaded connections.

BENEFITS

- Zinc-free
Environmentally friendly in cured form
Mixes easily
Workable consistency in excess of one hour
Water resistant
Oxidation resistant
Withstands high break-out torque
Provides a leakproof seal and strong permanent bond
Self lubricating
Unaffected by vibration, pounding or temperature
Excellent adhesion

APPLICATION

- 1. Thoroughly clean male and female threads to remove all thread dope, oil, and grease.
2. Dry threads completely prior to application of 252 Liqui-Lok.
3. Thoroughly mix contents of can; add entire bottle of hardener and continue mixing until completely uniform.
4. When used in conjunction with float equipment, apply 252 Liqui-Lok to male threads using a putty knife or spatula.
5. Make up joints final torque without delay.

NOTE

Setting action begins immediately after addition of the hardener. The mixture will remain in a workable consistency from 45 minutes to 2 hours under average conditions.

TYPICAL OBSERVATIONS 252

Table with 2 columns: Property and Value. Includes Chemical Family (Epoxy Polymer Resin), Color (Gray), Appearance (Paste), ASTM Penetration @ 77°F (25°C) (360), Type Curing (Thermo Curing), Density lb/gal (11.51), Specific Gravity @ 25°C (1.38), Flash Point (>400°F (>204°C)), Solubility in Water (Insoluble), Friction Factor (1.3), Shelf Life (unopened container) (Two years).

TYPICAL OBSERVATIONS 252 Hardener

Table with 2 columns: Property and Value. Includes Appearance (Liquid), Color (Pale Straw Colored), Odor (Aminic), Density, lb/gal @ 77°F (25°C) (8.51), Specific Gravity (1.02), Solubility in Water (Appreciable (>10%)), Percent Volatile (Nil), Flash Point (>200°F (>93°C)).

COVERAGE CHART

(FOR 1 POUND KIT)

Table with 2 columns: PIPE SIZE and NO. OF JOINTS. Lists pipe sizes from 4 1/2 inch to 16 inch and corresponding joint counts.

(FOR 1/2 POUND KIT)

Table with 2 columns: PIPE SIZE and NO. OF JOINTS. Lists pipe sizes from 4 1/2 inch to 16 inch and corresponding joint counts.

RELATED PRODUCTS

250 Liqui-Lok Thread Locking Compound



© 2012, BALMAR LLC Made in U.S.A. WARRANTY Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us.

Manufactured by BALMAR LLC 616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507 Sales Locations: LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

*Registered trade name of Oil Center Research, Inc. 03/20/18 The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes.