

# TK-3 Proximity System Test Kit

Bently Nevada\* Asset Condition Monitoring

---



## Description

The TK-3 Proximity System Test Kit simulates shaft vibration and position for calibrating Bently Nevada monitors. It verifies the operating condition of the monitor readouts as well as the condition of the proximity transducer system. A properly calibrated system ensures that the transducer inputs and the resulting monitor readings are accurate.

The TK-3 uses a removable spindle micrometer assembly to check the transducer system and position monitor calibration. This assembly features a universal probe mount that will accommodate probe diameters from 5 mm to 19 mm (0.197 in to 0.75 in). The mount holds the probe while the user moves the target toward or away from the probe tip in calibrated increments and records the output from the Proximitor\* Sensor using a voltmeter. The spindle micrometer assembly also features a convenient magnetic base for ease of use in the field.

Vibration monitors are calibrated using the motor-driven wobble plate. A swing-arm assembly located over the wobble plate holds the proximity probe in place. This assembly uses a universal probe mount, identical to that used with the spindle micrometer assembly. By using the absolute scale factor of the proximity probe in conjunction with a multimeter, the user adjusts the probe to find a position where the desired amount of mechanical vibration (as determined by peak-to-peak DC voltage output) is present. No oscilloscope is needed.

The user can then compare a vibration monitor's reading to the known mechanical vibration signal input viewed by the proximity probe. The mechanical vibration signal from the TK-3 can range from 50 to 254  $\mu\text{m}$  (2 to 10 mils) peak-to-peak.

---

## Specifications

### Power Requirements

*Electric:*

95-125 Vac, 50/60 Hz, 1A  
minimum

190-250 Vac, 50/60 Hz, 1A  
minimum

*Air:*

90 psi (6.2 bar) maximum

### Wobulator Range

*Vibration  
Amplitude  
Range:*

50 µm to 254 µm (2 to 10 mils)  
peak-to-peak.

### Maximum Speed

*Electric:*

0 to 5000 cpm ± 1000 cpm

*Air:*

0 to 5000 cpm ± 1000 cpm

### Spindle Micrometer Range:

0 – 25.4 mm (0 – 1000 mils).

### Target Button and Wobble Plate:

AISI 4140 Alloy Steel.

**NOTE:** Contact your nearest Sales  
Professional for details on special target  
and wobble plate materials.

### Physical Size

*Height:*

195 mm (7.68 inches)

*Width:*

299 mm (11.8 inches)

*Depth:*

248 mm (9.76 inches)

*Weight:*

5.22 kg (11.5 lb)

### Environmental

#### *Operational Temperature Range*

0 °C to 54 °C (32 °F to 130 °F)

#### *Storage Temperature Range*

-18 °C to 65 °C (0 °F to 150 °F)

#### *Humidity*

95% Non-Condensing Humidity

#### *Exposure*

Designed to meet IP54 for dust  
and water exposure (closed)

---

## CE Mark Directives

EMC Directives 2004/108/EC – with amendments

#### **IEC/EN61000-6-2**

#### **Electrostatic Discharge**

EN61000-4-2 Criteria A

#### **Electro-Magnetic Field (Radiated Immunity)**

EN61000-4-3 Criteria A

### **Electrical Fast Transient Burst**

EN61000-4-4  
AC Power Cable, Criteria B  
Line to Ground, Criteria B  
Neutral to Ground, Criteria B  
Protective Earth to Ground,  
Criteria B  
Line/Neutral/Protective Earth to  
Gnd, Criteria B

### **Surge Capability**

EN61000-4-5  
AC Power Ports, Criteria A

### **Conducted Immunity**

EN61000-4-6  
AC Power, Criteria A

### **Voltage Dips and Interrupts**

EN61000-4-11  
40%, 10 Cycles (200 mS) Criteria A  
70%, 25 Cycles (500 mS) Criteria C  
0%, 250 Cycles (5 Sec), Criteria C

### **IEC/EN61000-6-4**

#### **Radiated Emissions**

EN61000-6-4

#### **Conducted Emissions**

EN61000-6-4

### **Low Voltage Directive**

IEC/EN 61010-1

---

## **Ordering Information**

---

### **Electric Driven TK-3e**

#### **177313 – AXX – BXX**

**A:** Scale Units  
01 English  
02 Metric

**B:** Power Cord Type  
01 American  
02 European

---

### **Air Driven TK-3g**

#### **177314 – AXX**

**A:** Scale Units  
01 English  
02 Metric

---

## **Accessories**

### **168836**

MDS 100 – Data Acquisition CBT  
(Computer Based Training)  
Module

---

\* denotes trademarks of Bently Nevada, Inc., a wholly owned subsidiary of General Electric Company.

© 2007- 2013 Bently Nevada, Inc. All rights reserved.  
Printed in USA. Uncontrolled when transmitted electronically.

1631 Bently Parkway South, Minden, Nevada USA 89423  
Phone: 775.782.3611 Fax: 775.215.2873  
[www.ge-mcs.com/bently](http://www.ge-mcs.com/bently)