

NEXUS fall arrest 2 point harness

H32

Standard two point fall arrest harness

Features:

- · Contoured fit for comfort and freedom of movement
- 'Twist through' leg strap buckles
- · Contrasting colour leg and torso webbing
- · Integral lanyard parking points
- · Front and rear attachment points

Chest strap rings orientate the webbing for secure fit and optimal comfort.

Front attachment point is suitable for fall arrest, vertical systems and rescue.

The 'twist through' leg strap buckles allow the leg loops to be completely unfastened so the harness can be put on without stepping through the straps.

Shoulder buckles allow quick and easy adjustment with one hand.

Contrasting colour of leg and torso webbing assists correct fitting of harness for less experienced user.

Option:

H32Q - Quick Connect H32QJ - Quick Connect with additional features



Specifications:

NB: specifications and colour may change without notice.

Size: Universal Attachment Points:

EN Test Mass: 140kg

Dorsal

Stepnel

Sternal

Loading: Fall Arrest load

Conformity: EN361:2002 Harness Measurements (cm):

 Materials:
 Polyamide & Stainless Steel
 Torso
 78-115

 Weight (kg):
 1.10
 Thigh
 60-100

Industries: All general work at height

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997

sales support: admin@heightec.com heightec.com PDS153 22/06/22