

ASTRA K'biner steel offset, tri-act, captive bar

CKS4

Triple action karabiner offset D with optional captive bar

Features:

- Steel
- Zinc plated
- Triplelock
- Gate Opening: 24mm
- Overall Size: L 113mm, W 72mm, Ø 12mm
- Offset 'D'
- Optional Captive bar

Steel for strength.

Zinc plated for corrosion protection.

Triple action gate is self closing and locking and allows one handed operation. To open gate requires 3 separate actions, virtually eliminating the risk of accidental opening.

Supplied with separate captive bar which can be fitted by the user if required.

The captive bar is used to fix the karabiner to the rope etc. to prevent loss or disassembly. It also keeps the loading close to the spine (thus reducing any loss in strength).

Hook free gate to minimise snagging.

Also available alternative gate types:

CKS2 - Screwgate CKS3 - Twistlock



Specifications:

Size:	L 113mm, W 72mm, Ø 12mm
EN Test Mass:	n/a
Loading:	45kN major axis 7kN minor axis
Conformity:	EN362:2004/B
Materials:	Zinc plated steel
Weight (kg):	0.21
Industries:	Used in all work at height industries and rescue
All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable	

NB: specifications and colour may change without notice.

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997

sales support: admin@heightec.com

heightec.com