


Adapters

F3MK4 Male stud connector

BSPP 60° Cone end (ISO 8434-6) / Male BSPT thread (ISO 7)



Thread BSPP T4	Thread BSPT T3	A mm	C mm	D mm	L mm	Weight (steel) g/1 piece	Adapter Steel	Adapter Stainless Steel	PN (bar)
1/8	1/8	10	14	4	24	15	2F3MK4S	2F3MK4SS	315
1/8	1/4	15	14	4	29	28	2-4F3MK4S	2-4F3MK4SS	315
1/4	1/4	15	19	5	33	31	4-4F3MK4S	4-4F3MK4SS	315
1/4	1/8	10	19	5	29	27	4F3MK4S	4F3MK4SS	315
1/4	3/8	15	19	5	33	44	4-6F3MK4S	4-6F3MK4SS	315
3/8	3/8	15	22	8	35	52	6-6F3MK4S	6-6F3MK4SS	315
3/8	1/2	19	22	8	40	68	6-8F3MK4S	6-8F3MK4SS	160
3/8	1/4	15	22	7	35	48	6F3MK4S	6F3MK4SS	315
1/2	1/2	19	27	11	43	79	8-8F3MK4S	8-8F3MK4SS	160
1/2	3/8	15	27	11	39	68	8F3MK4S	8F3MK4SS	200
5/8	1/2	19	30	14	46	101	10F3MK4S	10F3MK4SS	200
5/8	3/4	19	30	14	46	102	10-12F3MK4S	10-12F3MK4SS	160
3/4	1/2	19	32	17	46	111	12-8F3MK4S	12-8F3MK4SS	315
3/4	3/4	19	32	17	46	126	12F3MK4S	12F3MK4SS	160
3/4	1	24	36	17	51	242	12-16F3MK4S	12-16F3MK4SS	120
1	3/4	19	41	22	50	173	16-12F3MK4S	16-12F3MK4SS	120
1	1	24	41	22	55	219	16F3MK4S	16F3MK4SS	120
1 1/4	1 1/4	25	50	29	64	337	20F3MK4S	20F3MK4SS	105
1 1/2	1 1/2	26	55	33	69	497	24F3MK4S	24F3MK4SS	105

Order codes shown are part of our current manufacturing programme.
Imperial and metric parts may vary in hexagon dimensions.

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Pressure ratings – PN shown, apply to Steel and Stainless Steel versions of the product.