

# MAXPROBE

## Pipeline Inspection System



The MaxProbe is packed with innovative and helpful features to enhance user efficiency and provides everything you need to carry out a professional drainage survey.

Technical Data - Maxprobe	
Cable length	50 / 60 m
Meterage counter	yes
Driving Force	Manual (push Rod)
Voltage	12v DC / 230v AC / 115v AC
Current	Ex Power Supply - 1.7A Max
Battery	Li-ion (9hrs running time)
Operating Temp	-10°C to +50°C
Charging Temp	0°C to +40°C
Weight	Reel - 23.5kg Box - 5.5kg approx.
Dimensions	Reel - 1010 x 415 x 625 mm Box - 360 x 290 x 160 mm
LCD size	10.4" (diagonal)
Resolution	800 x 600 RGB (SVGA)
LCD viewing angle	85° Typical
IP Rating	IP64 - open / closed
Storage	32Gb HDD standard x2 USB 2.1 x1 SD x1 Ethernet
Software	WinCan Embedded
Output	800 x 600 SVGA. DE15 socket
Video Format	MPEG4
Image Format	JPEG



Issue Date March 2016  
Subject to change without prior notice.

## FOCUSING ON THE FUTURE



Scanprobe Techniques Ltd  
Unit 11, Kenley Trade Park, Old Barn Lane, Kenley, Surrey CR8 5AU  
Tel: 020 3253 2001 Fax: 020 8660 5074

[www.scanprobe.com](http://www.scanprobe.com)

